

Ligna

A warm wood appearance tile which provides acoustic and fire safe properties, available in three finishes: Dark Beech, Light Beech and Classic Beech.

Ligna

A warm wood appearance tile which provides acoustic and fire safe properties, available in three finishes: Dark Beech, Light Beech and Classic Beech.


Ligna is available in three colours which can provide offices, showrooms and lobbies with an exclusive natural look. Smooth, non

perforated surfaces with the appearance of wood and all of the fire safety and acoustic benefits of stone wool.

ASSORTMENT

Edge detail	Module size (mm)	Product code	Weight (kg/m ²)	MS* / MS* easy access (mm)	Installation system
 A15	600 x 600 x 20	-	1.7	50 / 100	RockLink 15
	1200 x 600 x 20	-	1.7	50 / 100	
 A24	600 x 600 x 20	-	1.7	50 / 100	RockLink 24
	1200 x 600 x 20	-	1.7	50 / 100	
 E15	600 x 600 x 20	-	2.7	58 / 100	RockLink 15 RockLink Integra
	600 x 600 x 20	-	2.7	58 / 100	
 E24	600 x 600 x 20	-	2.7	58 / 100	RockLink 24 RockLink 24 FasTrac
	600 x 600 x 20	-	2.7	58 / 100	

* MS - Minimum Suspension



Light Beech



Classic Beech



Dark Beech





SOUND ABSORPTION

Sound absorption has been measured in accordance with ISO 354. Sound absorption data α_p , α_w and absorption class are calculated in accordance with ISO 11654. Noise Reduction Coefficient (NRC) is calculated in accordance with ASTM C423.



FIRE PERFORMANCE

General: Rockfon ceiling tiles have a core of stone wool. Stone wool is non-combustible with a melting point of more than 1000°C.

Reaction to fire: Class A1 in accordance with EN 13501-1.

Fire protection: The fire resistant properties of stone wool ensure Rockfon ceiling tiles provide fire protection in construction. The fire protection properties of Rockfon ceilings have been tested and classified in accordance with European norm EN 13501-2 and/or national norms depending on requirements in national building codes.



HUMIDITY RESISTANCE AND DIMENSIONAL STABILITY (FLEXURAL TENSILE STRENGTH)

Rockfon ceiling tiles are dimensionally stable even at humidity levels of up to 100% RH and can be installed at all temperatures ranging from 0°C to 40°C. No acclimatisation is necessary.

Ligna is predominantly classified as Class 1/C/0N in accordance with BS EN 13964. However, certain module sizes (width above 700mm) are Class 2/C/0N.



HYGIENE

Stone wool has no nutritional value and therefore it provides no sustenance to harmful micro-organisms.



CLEANING

The surface can be vacuum cleaned with a soft brush attachment.



ENVIRONMENT

A representative selection of Rockfon products have been awarded the Indoor Climate Label and the Finnish Indoor Climate Label (M1). Ligna is recyclable.



>

>